

DOES YOUR POOL MEET SAFETY STANDARDS?	×
The outside of the pool fence is at least 1200mm high all the way around	
If a boundary fence forms part of the pool fence; it must be at least 1800mm high	
The gap between the bottom of the fence and the ground is no more than 100mm	
All vertical or near-vertical rails on the fence are less than 100mm apart	
There are no potential hand holds or foot holds within 900mm of the top of the pool fence in any direction.	
There must be a 300mm clearance from the barrier inside the pool area	
Fencing materials with opening greater that 100mm shall not be used	
The pool fence is well-maintained and in a good state of repair (eg, it has no holes, broken rails or palings)	
The gate swings freely, and closes and latches by itself from any position	
The gate latch is working well so that the gate is secure and, once closed, can't be pulled open	
The gate opens outwards, away from the pool area	
The gap between the vertical barriers of a gate is no more than 100mm	
The gate latch release hieght reinforced must be at least 1400mm above any lower foothold	
Are you aware that it is dangerous and against the law to prop the gate open.	
If a wall forms part of the barrier, then there should not be an opening greater than 100mm	
Any openings (within the 1800mm height) in the window shall be permanently restricted to a maximum of 100mm.	
Any openings (within 1800mm height) shall be permanently restricted to a maximum of 100mm.	
There is an appropriate warning sign, including details of resuscitation (CPR) techniques, in the immediate vicinity of the pool area which can be easily read from a distance of 3 metres.	
Your pool fence is clear of any objects such as BBQs, trees, rocks, shrubs and deckchairs that could help a small child climb over the fence	

An owner may install the pool only after a safety barrier is installed and checked by a licensed building surveyor.

